

## MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber PanelMax Drywall Primer K21049225  
Revision Date: January 1, 2012

### 1. Product and Company Identification

**Product Name:** GRABBER® K21049225 PanelMax Drywall Primer

**Supplier:** THE SHERWIN-WILLIAMS COMPANY  
KRYLON PRODUCTS GROUP  
Cleveland, OH 44115

**Emergency telephone number:** (216) 566-2917

**Technical phone number:** 800-877-TURN (Concord, California) 8:00 a.m. - 4:00 p.m PST

**Regulatory Information** (216) 566-2902 [www.paintdocs.com](http://www.paintdocs.com)

**Medical Emergency** (216) 566-2917

**Transportation Emergency\*** 1(800) 424-9300

\*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)

### 2. Composition/Information on Ingredients

No ingredients in this product are hazardous as defined by the Department of Labor.

### 3. Hazards Identification

#### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist

#### EFFECTS OF OVEREXPOSURE

**EYES:** Irritation.  
**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system.

#### HMIS Codes

<b>Health</b>	1
<b>Flammability</b>	0
<b>Reactivity</b>	0

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

#### CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

### 4. First Aid Measures

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber PanelMax Drywall Primer K21049225  
Revision Date: January 1, 2012

## 5. Fire Fighting Measures

<b>FLASH POINT</b>	<b>LEL</b>	<b>UEL</b>	<b>EXTINGUISHING MEDIA</b>
Not Applicable	N.A.	N.A.	Not Applicable

### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

### K21049225

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## 6. Accidental Release Measures

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent.

## 7. Handling and Storage

### STORAGE CATEGORY

Not Available

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## 8. Exposure Controls/Personal Protection

### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.  
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.  
Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed as Dust in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH-ILV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), Osh-IA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

### RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

### PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

### EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

### OTHER PRECAUTIONS

Wear safety spectacles with unperforated sideshields.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber PanelMax Drywall Primer K21049225  
Revision Date: January 1, 2012

## 9. Physical and Chemical Properties

PRODUCT WEIGHT	8.46 lb/gal	1014 g/l
SPECIFIC GRAVITY	1.02	
BOILING POINT	212-500 F	100-260 C
MELTING POINT	Not Available	
VOLATILE VOLUME	83%	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A	
pH	9.5	

### VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)

0.67 lb/gal	81 gll	Less Water and Federally Exempt Solvents
0.12 lb/gal	14 gll	Emitted VOC

## 10. Stability and Reactivity

**STABILITY — Stable**

### CONDITIONS TO AVOID

None known.

### INCOMPATIBILITY

None known.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

### HAZARDOUS POLYMERIZATION

Will not occur

## 11. Toxicological Information

### CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NIP or OSHA listed carcinogen.

### TOXICOLOGY DATA

No LC50 or LD50 data available.

## 12. Ecological Information

### ECOTOXICOLOGICAL INFORMATION

No data available.

## 13. Disposal Considerations

### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## 14. Transport Information

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

Not Regulated for Transportation.

### Canada (TDG)

Not Regulated for Transportation.

### IMO

Not Regulated for Transportation.

### IATA/ICAO

Not Regulated for Transportation.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Grabber PanelMax Drywall Primer K21049225  
Revision Date: January 1, 2012

## 15. Regulatory Information

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.			

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed. or are exempt from listing, on the TSCA Inventory.

## 16. Other Information

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.